



## Xcalibur EL/SL Jar Calibration Report

Date:	<b>11.10.09</b>
-------	-----------------

Model	<b>XC</b>					Serial No.	<b>XC09-0053</b>
Size:	<b>1.562</b>	EL	<b>X</b>	SL		Tech Signature:	<b>Jon Morgan</b>
Base, District Manager, or Engineering Manager's Signature:							<b>Jeff Kimberly</b>

**General Data:**

Pin Connection	<b>TITAN ATF GO 400°</b>
Box Connection	<b>TITAN ATF GO 400°</b>
Retracted Length	<b>75 ¾"</b>
Extended Length	<b>81 ¾"</b>
Weight	<b>31 lbs.</b>

**\*\*Acceptable maximum and minimum setting levels\*\***

	Min	Max	
	200/300	1350/1700	1-9/16" Xcalibur S/L
	200/300	1350/1700	1-9/16" Xcalibur E/L
	350/450	1500/1800	2-3/4" Xcalibur E/L

**Deviation from Maximum/Minimum settings:**

Accepted by Base, District Manager, or Engineering Manager: \_\_\_\_\_

Turns	Calibration Test #1	Calibration Test #2	Final Setting
0			<b>300</b>
1/2			<b>400</b>
1			<b>500</b>
1 1/2			<b>600</b>
2			<b>700</b>
2 1/2			<b>800</b>
3			<b>900</b>
3 1/2			<b>1000</b>
4			<b>1100</b>
4 1/2			<b>1200</b>
5			<b>1300</b>
5 1/2			<b>1400</b>
6			<b>1450</b>
6 1/2			<b>1550</b>
7			<b>1650</b>
7 1/2			<b>1750</b>
8			