




DIMENSION BID

Slickline Assistant Onshore On-the-Job Training Record

Trainee's Name:	AMMAN UTHMAN R.S. ABDUL WAKIM	Job Title:	TSB
Month:	October	Training Period:	

No.	Main Tasks (please describe tasks and specify name of tools / equipment)	Training Date	Training Time		Total Hours	PR*	Signature	
			From	To			Trainee	Instructor
1	- assist PCE for Reaming equipment at load out to CMC Bredid line job	01/10/2023	08:00	17:00				
2	- Recover the loose of compressor air outlet at AC#17 - Function test AC#17 (ESD/shutdown button) and prepare of acceptance at 01/10/2023 - Function test powerpack V04272 (overspeed, ESD button, shutdown button)	01/10/2023	08:00	17:00				
3	- Acceptance AC#17 with client - Learn how to connect hose from PowerPack to insulative tank to wireline mast 70ft	01/10/2023	08:00	17:00				

DIMENSION BID

<p>A</p> <ul style="list-style-type: none"> - Rig up wireline mast 74ft - Learn about Erecting Procedure and lowering procedure of mast 		11/10/2023	0800	1700		AJ	
<p>S</p> <ul style="list-style-type: none"> - Housekeeping of surface equipment area 		12/10/2023				AJ	

* Performance Rating (PR): S - Strong A - Adequate NI - Improvement Needed

Total Hours

Approved by:

R

Overall Assessment:

Designation

#m

Date

12/10/23

8/10/2023 to 12/10/2023

Rig up Mast Procedure

Erecting Procedure

1. Remove all lifting slings from the mast and store them in the mast storage box.
2. Position front outriggers and attach front spreader bars.
3. Attach guy ropes to the top of the mast crown and tighten turnbuckle to tension guy ropes.
4. Position jacking feet on outriggers and level mast. Ensure the mast frame is supported in all corners.
5. Ensure the external Power Pack is running.
6. Connect all hydraulic hoses to the bulkhead (auxiliary hose must be connected).
7. Select mast Erect Functions and erect the mast to just past the vertical position and ease back on the control lever to slow down the mast movement when approaching the vertical position.
8. Select winch function and lower off hook as and when required whilst extending mast.

Lowering Procedure

1. Remove locking pin and slowly bring mast back to almost the vertical position.
2. Stop and raise hook when necessary.
3. When mast is fully retracted, attach hook to its fixing point before lowering the boom to its horizontal transportation position.
4. Care must be taken when lowering mast not to foul the guy ropes.
5. Remove all guy ropes and accessories and store in storage box. Fold away all outriggers and secure at the relevant fixing points.
6. Attach lifting sling set to frame pad eyes.