



ADDRESSABLE RELEASE TOOL - TOOL TYPE TABLE

Tool Type:	Pressure:	Temp:	Dia:	Max. Voltage:	Max. Current:	Length (Make-up):	Head Type:	SWL:	Primary Applications:
ART-C	15ksi	177 °C (350 °F)	1 11/16"	1500vdc / 1000vac	5A	19.6"	GO A	4400lbs	C/H Logging, Production Logging
ART-D	18ksi	177 °C (350 °F)	2 1/8"	1500vdc / 1000vac	12A	33"	GO B	6700lbs	Tractors, Ballistics
ART-G	15ksi	177 °C (350 °F)	1 11/16"	1500vdc / 1000vac	12A	19.6"	BA-A3	4400lbs	C/H Logging, Production Logging
ART-H	18ksi	177 °C (350 °F)	2 1/8"	1500vdc / 1000vac	12A	27.0"	GO A	6700lbs	Tractors, Ballistics
ART-F	18ksi	177 °C (350 °F)	2 1/8"	1500vdc / 1000vac	12A	27.0"	BA-A3	6700lbs	Tractors, Ballistics
ART-J	18ksi	177 °C (350 °F)	2 3/4"	1500vdc / 1000vac	12A	30.7"	BA-A2	6700lbs	Tractors, Ballistics
ART-T	18ksi	200 °C (392 °F)	2 1/8"	1500vdc / 1000vac	12A	30.7"	GO A	6700lbs	HPHT Operations, Ballistics
MRT-X	20ksi	177 °C (350 °F)	3 3/8"	1500vdc / 1000vac	5A	35.3"	See (1)	35,000lbs	O/H Logging
ACP-A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Control Panel for ART/MRT only
MPP-B	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Control Panel for ART / MRT / PSJ / GBS / IDC

Notes:

1) MRT length excludes heads. SLB-31, SLB-10, BA-10, WFD-55, BA-A2 heads are available.