



## Xcalibur EL/SL Jar Calibration Report

Date:	<b>7.22.10</b>
-------	----------------

Model	<b>XC</b>					Serial No.	<b>XC08-0023</b>
Size:	<b>2.75</b>	EL	<b>X</b>	SL		Tech Signature:	<b>Matthew Ledet</b>
Base, District Manager, or Engineering Manager's Signature:							<b>Duanyell Williams</b>

**General Data:**

Pin Connection	<b>Titan ATF 400°</b>
Box Connection	<b>Titan ATF 400°</b>
Retracted Length	<b>59 ¾</b>
Extended Length	<b>66 ¼</b>
Weight	<b>68 lbs</b>

**\*\*Acceptable maximum and minimum setting levels\*\***

	Min	Max	
	200/300	1350/1700	1-9/16" Xcalibur S/L
	200/300	1350/1700	1-9/16" Xcalibur E/L
	350/450	1500/1800	2-3/4" Xcalibur E/L

**Deviation from Maximum/Minimum settings:**

Accepted by Base, District Manager, or Engineering Manager: \_\_\_\_\_

Turns	Calibration Test #1	Calibration Test #2	Final Setting
0		<b>400</b>	
1/2		<b>500</b>	
1		<b>575</b>	
1 1/2		<b>675</b>	
2		<b>725</b>	
2 1/2		<b>825</b>	
3		<b>925</b>	
3 1/2		<b>1000</b>	
4		<b>1075</b>	
4 1/2		<b>1125</b>	
5		<b>1225</b>	
5 1/2		<b>1275</b>	
6		<b>1350</b>	
6 1/2		<b>1450</b>	
7		<b>1525</b>	
7 1/2		<b>1575</b>	
8		<b>1675</b>	