



Xcalibur EL/SL Jar Calibration Report

Date:	10.7.11
-------	----------------

Model	XC					Serial No.	XC09-0049
Size:	1.562	EL	X	SL		Tech Signature:	Matt ledet
Base, District Manager, or Engineering Manager's Signature:							Jeff Kimberly

General Data:

Pin Connection	TITAN ATF GO 400°
Box Connection	TITAN ATF GO 400°
Retracted Length	75 3/4"
Extended Length	81 3/4"
Weight	31 lbs.

****Acceptable maximum and minimum setting levels****

	Min	Max	
	200/300	1350/1700	1-9/16" Xcalibur S/L
	200/300	1350/1700	1-9/16" Xcalibur E/L
	350/450	1500/1800	2-3/4" Xcalibur E/L

Deviation from Maximum/Minimum settings:

Accepted by Base, District Manager, or Engineering Manager: J. Kimberly

Turns	Calibration Test #1	Calibration Test #2	Final Setting
0	300	225	
1/2	375	375	
1	450	450	
1 1/2	550	525	
2	650	600	
2 1/2	725	725	
3	850	825	
3 1/2	900	900	
4	1000	975	
4 1/2	1075	1075	
5	1175	1175	
5 1/2	1275	1275	
6	1350	1350	
6 1/2	1450	1450	
7	1525	1525	
7 1/2	1650	1650	
8	1750	1725	



Xcalibur EL/SL Jar Calibration Report

Date:	10.6.11
-------	----------------

Model	XC				Serial No.	XC09-0065
Size:	1.562	EL	X	SL	Tech Signature:	Matt Ledet
Base, District Manager, or Engineering Manager's Signature:						Jeff Kimberly

General Data:

Pin Connection	TITAN ATF GO 400°
Box Connection	TITAN ATF GO 400°
Retracted Length	75 3/4"
Extended Length	81 3/4"
Weight	31 lbs.

****Acceptable maximum and minimum setting levels****

	Min	Max	
	200/300	1350/1700	1-9/16" Xcalibur S/L
	200/300	1350/1700	1-9/16" Xcalibur E/L
	350/450	1500/1800	2-3/4" Xcalibur E/L

Deviation from Maximum/Minimum settings:

Accepted by Base, District Manager, or Engineering Manager: _____

Turns	Calibration Test #1	Calibration Test #2	Final Setting
0	250	225	
1/2	325	325	
1	425	425	
1 1/2	525	525	
2	600	600	
2 1/2	725	725	
3	800	800	
3 1/2	900	875	
4	1000	950	
4 1/2	1100	1050	
5	1200	1125	
5 1/2	1325	1225	
6	1400	1300	
6 1/2	1475	1400	
7	1575	1550	
7 1/2	1650	1625	
8	1725	1700	